



RAIMONDI

SINCE 1974 INNOVATIONS FOR
THE TILE SETTING PROFESSIONAL

raimondispa.com

RAIZOR **MTC 2X**


MODULAR TILE CUTTER
FOR TILES UP TO 153 cm (5')



NEW



RAIZOR MTC2X - MODULAR CUTTING SYSTEM FOR TILES UP TO 153 cm (5')




Ø20 mm (3/4")
titanium-coated wheel



PREMIUM pliers for 3-15 mm (1/8" - 19/32")
thick tiles included

- Modular rail cutting system for cutting regular size tiles.
- Consisting of 2 combinable rails; each rail allows to cut tiles up to 66 cm (2.2') long. Connect rails to reach length of cut up to 153 cm (5').
- Raazor MTC2X consists of:
 - Two rails providing each length of cut up to 66 cm (2.2'); each equipped with 2 dual-lip suction cups with release tab;
 - PREMIUM pliers for cutting tiles from 3 to 15 mm (1/8" - 19/32") thick;
 - Die-cast aluminum cutting unit running on two rails and provided with spring pin scoring element. Complete with Ø 20 mm (25/32") titanium-coated wheel (wheel with built-in bearing and calibrated high-strength steel screw);
 - all packed into a padded bag (length 110 cm - 3.6') with shoulder straps and internal pocket (possibility to carry up to 4 guides).
- In order to provide optimal grip on tile of any size, each rail is equipped with 2 x Ø 95 mm (3.7") dual-lip suction cups featuring stain-free rubber. Suitable for moderately textured materials as well (4 suction cups in total).
- In addition to being very useful when measuring the cut to be made, the suction cups prevent Raazor MTC2X from moving during the incision, thus ensuring maximum precision and efficacy. Moreover, thanks also to their unique positioning inside aluminium guides, they prevent the guide from overturning regardless of the pressure applied to the cutting unit and the cutting position. This makes Raazor MTC2X effective even for the most complicated cuts and for very thick tiles.
- The cutting unit slides on the guide thanks to 3 resin wheels with high mechanical performance, each equipped with 2 bearings. The adjustment system it is equipped with allows for perfect parallelism between the scoring wheel and the rail, eliminating any play. This allows both to eliminates any kind of play and to perfectly align the titanium-coated cutting-wheel to the rail resulting in maximum efficacy, precision and quality of cut.
- The Ø 20 mm (3/4") scoring wheel features a special Titanium coating which gives it extremely high wear resistance; it is also equipped with a built-in bearing to ensure maximum smoothness, extreme precision and efficacy, and simple and fast replacement.
- Each suction cup has a release tab that can be used if it gets stuck.
- Suction cup handles with 180° movement so as not to interfere with the carriage stroke.
- Distance between the incision line and the aluminium profile: 20 mm (3/4").
- The bag protects the product and allows it to be carried easily. It also features a pocket for personal items or work tools.
- Supplied with PREMIUM progressive pressure pliers for cutting tiles from 3 to 15 mm (1/8" - 19/32") thick.
- To cut tiles more than 15 mm (19/32") thick, use the accessory pliers code 169TM01AN.
- Accessory extension (art. 433CP00M66) with 66 cm (2.2') cutting length.
- Available as an accessory is the Power-Raazor^{mkII} cutting unit to perform cuts with a diamond disc at 45° and 90° and intermediate angles.

Item		Description	length of cut		
433CP00AM2	1	Raazor MTC2X — modular cutting system for tiles (max cutting length: 153 cm - 5'). It includes: • 2 connectable guides with cutting length of 66 cm (2.2') each (tot. 153 cm - 5') with integrated double-lip suction cups (4 suction cups total); • die-cast aluminum cutting unit featuring dual-rail sliding and pin scoring element; Ø 20 mm (25/32") titanium wheel with built in bearing; • PREMIUM pliers for cutting tiles from 3 to 15 mm (1/8" - 19/32") thick; • padded bag (length 110 cm - 3.6') with shoulder straps and internal pocket (possibility to carry up to 4 guides).	1 guide max cutting length 66 cm (2.16')	112x19xh 26 cm 44"x 7.5"x 10.2"	6,7 Kg 14.7 lbs
			2 guides max cutting length 153 cm (5')		



RAIMONDI

Headquarter: Via R. Dalla Costa 300/A - ph. +39 059 280888 - info@raimondispa.com - raimondispa.com